

Profolene PE Banner



Profolene PE Banner film is a white, tough polyethylene substrate for single side printed advertising graphics. The film has excellent lay-flat characteristics and dimensional stability for precise print registration. Ideal for outdoor and cold weather applications. Superior UV resistance.

APPLICATIONS:

- Banners
- Pennants
- Advertising Graphics
- Cold Weather Applications
- Outdoor Graphics

ADVANTAGES:

- Superior lay-flat characteristics
- Better UV resistance
- Excellent dimensional stability
- Easy to print using a variety of methods including screen printing, offset lithography and flexography
- Low cost
- Easy to sew, grommet and heat seal
- Acid free - contains no PVC

MANUFACTURING CAPABILITIES:

- White film is standard
- In-line corona treatment on both sides
- Thickness range: 6 mil to 12 mil thick
- Standard web widths: 44" - 83"
- In-line slitting to custom roll widths
- Biodegradable available

The statements, technical information, and recommendations contained herein are presented in good faith based upon tests believed to be reliable and/or practical experience. The reader is cautioned that Profol cannot guarantee the accuracy or completeness of the information, and it is the customer's sole responsibility to determine the suitability of Profol's products in any given application.

American
profol® Inc.
A Profol Group Company

AP2008JANV1

4333 C Street SW · Cedar Rapids IA 52404
Phone: 319-365-0599 · sales@profol.com · www.profol.com

graphics